

## MEAN WELL - NPB-750-48 - 48V CANBus charger



**Reference** : MEA-NPB-750-48-750W

**Brand** : MEAN WELL

**Options** :

No variants

**3D Model** : Available

**EAN-13** : 3701234567891

The MEAN WELL NPB-750-48 is a high-reliability smart battery charger (~750W class) designed for 48V systems. It provides selectable 2- or 3-stage charging profiles (built-in curves + programmable profile), a wide charge voltage range (42–80V), and system-level control/monitoring interfaces (CANBus, logic I/O). For 16S LiFePO4 packs (48V nominal), the built-in “AGM/LiFePO4” preset targets a typical end-of-charge voltage of 58.4V, provided the final settings match the battery/BMS manufacturer recommendations.

### Overview

- 48V model: 42–80V charge voltage range, 11.3A max (CC), ~759W max.
- 2- or 3-stage charging (DIP switch) + programmable parameters (CC/CV/FV/TC, timeouts).
- Built-in LiFePO4 preset (“AGM/LiFePO4”): Vboost typically 58.4V.
- Auto-ranging (advanced mode) for lithium batteries with BMS.
- Interfaces: CANBus, Remote ON/OFF, TTL “Battery Full” and “Charger OK”, NTC (RTH).
- Protections: short-circuit, over-voltage, input under-voltage, battery under/over-voltage, over-temperature, reverse polarity.

### System integration

**Typical use:** 16S LiFePO4 packs (48V nominal) with BMS. A common end-of-charge voltage is around **58.4V** (16×3.65V). The NPB-750-48 supports this via the LiFePO4 preset and its 42–80V charge voltage window.

**Integration note:** final settings must follow **the battery/BMS manufacturer recommendations**. Validate on a test bench if needed.

- If float is not desired: use 2-stage mode or program FV (float) per your BMS/battery strategy.

- With 11.3A max, check the intended C-rate vs capacity.

## Charging profiles & settings

The charger provides **2-stage** (CC → CV) or **3-stage** (CC → CV → Float) charging. Built-in curves are selected via DIP switch; a profile can be customized (SBP-001 and/or CANBus depending on integration).

---

© EVEA Distribution – All rights reserved – [contact@evea-solutions.com](mailto:contact@evea-solutions.com)

This document is the exclusive property of EVEA Distribution. Any reproduction or distribution, even partial, is prohibited without prior written authorization.

The information contained in this datasheet is provided for information purposes only and may be modified without notice. This document does not constitute a contractual commitment.